


PP40-G1

Guitar Ra Transformer 8000Ω of 40W.


Caption

I_{max}	maximum current	UL	peel off the ultra-linear
L_{aa}	inductance of the anode-anode, $f=120\text{Hz}$	f_{min}	minimum frequency
R_o	load resistance	core	core type
weight	approximate weight	Z_{aa}	anode-anode impedance
R_{aa}	resistance of the anode-anode	P_{max}	maximum power
sizes	overall dimensions	price	price
f_{max}	maximum frequency	$k_{n:n}$	transmission

Specyfikacje



Push Pull - PP40-G1 - wersja z dwoma deklami (PL)							
P_{max}	Z_a	I_{max}	R_{aa}	UL	$k_{n:n}$	R_o	L_a
40 W	8000 Ω	150 mA	-	-	-	4, 8 and 16 Ω	-
f_{min}	f_{max}	Core	Size W	Size H	Size L	Weight	Count
30Hz @ -3dB	30kHz @ -3dB	EI84/42	W1 - 110 mm W2 - 110 mm W3 - 110 mm	H1 - 110 mm H2 - 110 mm	L1 - 110 mm L2 - 110 mm L3 - 110 mm L4 - 110 mm	2 kG	1



Push Pull - PP40-G1 - wersja z dwoma deklami (DE)

P_{max}	Z_a	I_{max}	R_{aa}	UL	$k_{n:n}$	R_o	L_a
40 W	8000 Ω	150 mA	-	-	-	4, 8 and 16 Ω	-
f_{min}	f_{max}	Core	Size W	Size H	Size L	Weight	Count
30Hz @ -3dB	30kHz @ -3dB	EI84/42	W1 - 110 mm W2 - 110 mm W3 - 110 mm	H1 - 110 mm H2 - 110 mm	L1 - 110 mm L2 - 110 mm L3 - 110 mm L4 - 110 mm	2 kg	1