


LO PP80-1

The transformer is made on the annealed cores, thickness of laminations 0.3 mm .

Caption

sizes	overall dimensions	$I_{max}$	maximum current
UL	peel off the ultra-linear	$k_{n:n}$	transmission
$L_{aa}$	inductance of the anode-anode, f=120Hz	core	core type
$Z_{aa}$	anode-anode impedance	price	price
$f_{max}$	maximum frequency	$R_{aa}$	resistance of the anode-anode
$R_o$	load resistance	$f_{min}$	minimum frequency
$P_{max}$	maximum power	weight	approximate weight

Specyfikacje



Push Pull - LO PP80-1							
$P_{max}$	$Z_a$	$I_{max}$	$R_{aa}$	UL	$k_{n:n}$	$R_o$	$L_a$
80 W	4000 $\Omega$	250 mA	120 $\Omega$	43 %	31.6 : 1, 22.3 : 1	4 and 8 $\Omega$	35 H
$f_{min}$	$f_{max}$	Core	Size W	Size H	Size L	Weight	Count
10Hz @ -3dB	60kHz @ -3dB	EI96/59	W1 - 80 mm W2 - 96 mm W3 - 110 mm	H1 - 80 mm H2 - 84 mm	L1 - 59 mm L2 - 90 mm L3 - 106 mm L4 - 94 mm	3.5 kG	1
Price							
1-5 units		5+ units		10+ units		25+ units	
115.0 USD		109.0 USD		103.0 USD		98.0 USD	